



FARMER

THE LIFELINE OF THE NATION



C.R.I. PUMPS

Pumping trust. Worldwide.



**HIGH
DISCHARGE
PUMP**



150mm / 175mm and 150mm / 200mm Submersible Pumpsets

COPPER ROTOR WITH SILVER BRAZING FOR LONGER LIFE



**Rigid & POWERFUL
MOTOR**



**CFD Designed BOWLS & CASTED
SS IMPELLERS** for high discharge



**Designed for WIDE
VOLTAGE OPERATION**



SELF LUBRICATED journal
BUSHES for Increased life

150mm / 175mm, 150mm /200mm & 200mm / 250mm Borewell Submersible Pumpsets - CONGO Series

C.R.I. Borewell Submersible Pumpsets are powered by water filled, rewindable submersible motor suitable for continuous duty. The stator is wound with special water proof synthetic film insulated copper winding wires and made up of low watt loss silicon steel laminations assembled under pressure and rigidly locked in stainless steel stator shell. T-Bolt design in all motor ensures rigid construction. Optimal design of impellers and diffusers offers best possible hydraulic efficiency. Built-in check valve prevents back flow and reduces the risk of water hammering.

This 175mm & 200mm submersible pumpsets are supplied with 150mm motor combination and 250mm submersible pumpsets are supplied with 200mm motor combination only.

SPECIFICATIONS	150mm/175mm	150mm/200mm	200mm/250mm
Power Range	4.5 kW - 15 kW (6HP - 20HP)	5.5 kW - 18.5 kW (7.5HP - 25HP)	30 kW - 75 kW (40HP - 100HP)
Speed	2900 rpm		
Version	Three phase 380 - 415V, 50Hz AC Supply		
Maximum total head	101 metre	88 metre	162 metre
Maximum flow rate	31 lps (111.6 m³/h)	33.33 lps (120 m³/h)	60 lps (216 m³/h)
Maximum outer diameter	165 mm	195 mm	247 mm
Nominal outlet size	100 mm	80, 100, 125 & 150 mm	150 mm
Degree of protection	IP 58		
Direction of rotation	Electrically Reversible		
Thrust load	4.5 kW - 15 kW - 3500 lbs	5.5 kW - 11 kW - 3500 lbs 15 kW - 18.5 kW - 6000 lbs	15 kW - 18.5 kW - 6000 lbs 22 kW - 75 kW - 10000 lbs
Type of duty	S1 (Continuous)		
Method of starting	D.O.L upto 5.5 kW, SD upto 15kW	SD 5.5 kW - 18.5 kW	SD 30 kW - 75 kW
Maximum starts per hour	20 times	10 times	10 times

SALIENT FEATURES

- High operating efficiency ● Dynamically balanced rotating parts ensures minimum vibration and longer life
- Extremely tough and hard wearing lubricated journal bearings are used ● Designed for wide voltage fluctuations
- Better efficiency and consistent performance ● Specially designed high performance thrust bearing(SS 420 with Graphite Carbon) to withstand high axial thrust load ● SS 410 impellers and hard chrome SS Sleeves are used to increase the life of the pump

APPLICATIONS

- Agriculture ● Domestic ● Irrigation ● Gardens ● Civil & Industrial water supply ● Rural Water Supply ● Ponds
- Firefighting ● Pressure boosting



CONGO

**2.16lac
litres/
per hour**

PERFORMANCE CHART

150mm / 175mm BOREWELL SUBMERSIBLE PUMPSETS - **CONGO Series**

2900 RPM, At Rated Voltage – **Three Phase** 415 Volts, 50hz, A.C. Supply, Maximum Outer Diameter : **165 mm**

MIXED FLOW

Model	kW	HP	Stage	Outlet Size in mm	m³/hr lps	0	10	20	30	40	50	60	65	70
						0	2.77	5.55	8.33	11.11	13.88	16.66	18.05	19.44
WC7CM-50/5/03S	3.7	5	3	100	Head in Metres	35.5	33.5	32	29.5	26	22.5	17.5	14	9.5

Model	kW	HP	Stage	Outlet Size in mm	m³/hr lps	0	18	23.98	27	33.01	39.02	45	51.01	56.98	63	69.01	74.98
						0	5	6.66	7.5	9.17	10.84	12.5	14.17	15.83	17.5	19.17	20.83
WC7CM-50/6/03	4.5	6	3	100	Head in Metres	40	35	34	33	31	30	28	26	25	23	21	18
WC7CM-50/7.5/04	5.5	7.5	4	100		45	41	41	40	39	37	35	31	29	26	22	18
WC7CM-50/10/05	7.5	10	5	100		62	56	53	52	49	47	45	42	40	38	35	31
WC7CM-56/6/02	4.5	6	2	100		30	29	28	27	25	23	21	20	19	18	17	15
WC7CM-56/7.5/03	5.5	7.5	3	100		41	37	36	35	34	32	31	29	28	26	24	22
WC7CM-56/10/04	7.5	10	4	100		52	48	46	45	42	41	39	37	36	34	32	31
WC7CM-56/12.5/05	9.3	12.5	5	100		67	62	60	59	56	54	51	48	46	43	40	36
WC7CM-56/15/06	11	15	6	100		74	71	69	69	67	65	63	60	58	55	51	48
WC7CM-56/17.5/07	13	17.5	7	100		88	84	82	81	78	76	73	70	68	64	61	57
WC7CM-60/10/03	7.5	10	3	100		46	42	41	40	39	37	36	34	33	31	29	27
WC7CM-60/12.5/04	9.3	12.5	4	100		63	57	55	54	52	49	47	44	43	40	38	35
WC7CM-60/15/05	11	15	5	100		75	69	67	66	64	61	59	56	53	51	48	45
WC7CM-60/17.5/06	13	17.5	6	100		85	78	76	75	72	70	67	64	61	57	53	49
WC7CM-60/20/07	15	20	7	100		99	91	89	88	85	81	78	73	69	65	61	57

Model	kW	HP	Stage	Outlet Size in mm	m³/hr lps	0	25.2	32.4	39.6	46.8	54	61.2	68.4	75.6	82.8	90	97.2	104.4	111.6
						0	7	9	11	13	15	17	19	21	23	25	27	29	31
WC7CM-61/7.5/02	5.5	7.5	2	100	Head in Metres	34	29	28	27	26	25	23	21	19	16	14	11		
WC7CM-61/12.5/03	9.3	12.5	3	100		55	47	46	44	42	41	39	37	34	30	26	21		
WC7CM-61/15/04	11	15	4	100		66	60	59	56	54	52	50	48	45	42	37	32		
WC7CM-61/20/05	15	20	5	100		80	71	69	67	65	62	60	56	51	45	39	31		
WC7CM-61/25/06	18.5	25	6	100		101	91	88	86	84	81	77	74	69	63	57	50	43	34

PERFORMANCE CHART

150mm / 175mm BOREWELL SUBMERSIBLE PUMPSETS - CONGO Series

2900 RPM, At Rated Voltage – **Three Phase** 415 Volts, 50hz, A.C. Supply, Maximum Outer Diameter : **165 mm**

MIXED FLOW

Model	kW	HP	Stage	Outlet Size in mm	m ³ /hr lps	0	25.2	32.4	39.6	46.8	54	61.2	68.4	75.6	82.8	90	97.2	104.4	111.6
						0	7	9	11	13	15	17	19	21	23	25	27	29	31
WC7CM-69/7.5/02	5.5	7.5	2	100	Head in Metres	39	34.5	33.5	32.5	31.5	30	28.5	26.5	24.5	22	19	16		
WC7CM-69/10/02	7.5	10	2	100		39	35	34	33	32	30	29	27	25	22	19	16		
WC7CM-69/12.5/03	9.3	12.5	3	100		54	48	47	46	44	43	42	40	38	35	32	28		
WC7CM-69/15/03	11	15	3	100		56	48	46	45	44	43	41	40	37	34	31	26		
WC7CM-69/20/04	15	20	4	100		77		75	70	65	61	57	54	51	48	44	38		
WC7CM-69/25/05	18.5	25	5	100		91	84	82	80	78	75	73	70	65	60	54	48	42	34

Model	kW	HP	Stage	Outlet Size in mm	m ³ /hr lps	0	25.2	32.4	39.6	46.8	54	61.2	68.4	75.6	82.8	90	97.2	104.4	111.6
						0	7	9	11	13	15	17	19	21	23	25	27	29	31
WC7CM-75/12.5/02	9.3	12.5	2	100	Head in Metres	41		36	35	34	33	31	29	27	24	21	19		

Model	kW	HP	Stage	Outlet Size in mm	m ³ /hr lps	0	25.2	32.4	39.6	46.8	54	61.2	68.4	75.6	82.8	90	97.2	104.4	111.6
						0	7	9	11	13	15	17	19	21	23	25	27	29	31
WC7CM-69/5/03 (SPL)	3.7	5	3	100	Head in Metres	39	34	33	32	30	28.5	26.5	24	21	18	14	11		
WC7CM-69/7.5/03(SPL)	5.5	7.5	3	100		45	39	38	37	36	35	33	31	28	25	22	18		
WC7CM-61/10/03(SPL)	7.5	10	3	100		48	43	42	41	40	38	36	35	33	29	25	22	19	15

PERFORMANCE CHART

150mm / 200mm BOREWELL SUBMERSIBLE PUMPSETS - CONGO Series

2900 RPM, At Rated Voltage – **Three Phase** 415 Volts, 50hz, A.C. Supply, Maximum Outer Diameter : **195 mm**

MIXED FLOW

Model	kW	HP	Stage	Outlet Size in mm	m ³ /hr lps	0	18	23.98	27	33.01	39.02	45	51.01	56.98	63	69.01	74.98	81	87.01
						0	5	6.66	7.5	9.17	10.84	12.5	14.17	15.83	17.5	19.17	20.83	22.5	24.17
WC8CM-50/10/3	7.5	10	3	100	Head in Metres	54	52	50	49	47	45	43	40	38	35	32	29	25	21

Model	kW	HP	Stage	Outlet Size in mm	m ³ /hr lps	0	20	30	40	50	60	65	68	70	80	90
						0	5.55	8.33	11.11	13.88	16.66	18.05	18.88	19.44	22.22	25
WC8CM-58/10/03	7.5	10	3	100	Head in Metres	56	50	48.5	46	43	38	34	32	27	20.5	13.5

Model	kW	HP	Stage	Outlet Size in mm	m ³ /hr lps	0	18	23.98	27	33.01	39.02	45	51.01	56.98	63	69.01	74.98	81
						0	5	6.66	7.5	9.17	10.84	12.5	14.17	15.83	17.5	19.17	20.83	22.5
WC8CM-60/7.5/2	5.5	7.5	2	100	Head in Metres	36	35	34	33.5	33	31	30	28	27	25		23	21
WC8CM-60/12.5/3	9.3	12.5	3	100	Head in Metres	60	55	53	52	51	49	48	47	46	45	44	41	39

Model	kW	HP	Stage	Outlet Size in mm	m ³ /hr lps	0	18	23.98	27	33.01	39.02	45	51.01	56.98	63	69.01
						0	5	6.66	7.5	9.17	10.84	12.5	14.17	15.83	17.5	19.17
WC8CM-65/12.5/03	9.3	12.5	3	100	Head in Metres	68	60	57	55	51	47	43	42	36	30	24
WC8CM-65/15/04	11	15	4	100	Head in Metres	84	77	73	68	64	58	53	51	44	35	26

Model	kW	HP	Stage	Outlet Size in mm	m ³ /hr lps	0	36.8	69.2	84.4	95.5	106.7	113.9	122.0
						0	10.23	19.21	23.44	26.54	29.65	31.64	33.88
WC8CM-68/10/2	7.5	10	2	100	Head in Metres	43.0	39.2	35.31	31.41	27.58	23.73	19.79	11.94

Model	kW	HP	Stage	Outlet Size in mm	m ³ /hr lps	0	24	54.4	74.1	85.2	84.1	94.9	110.9	120.2
						0	6.7	15.1	20.6	23.7	23.4	26.4	30.8	33.4
WC8CM-68/15/3	11	15	3	100	Head in Metres	67.2	61.2	56.4	51.5	46.6	41.6	36.8	31.8	22

PERFORMANCE CHART

150mm / 200mm BOREWELL SUBMERSIBLE PUMPSETS - CONGO Series

2900 RPM, At Rated Voltage – Three Phase 415 Volts, 50hz, A.C. Supply, Maximum Outer Diameter : 195 mm

MIXED FLOW

Model	kW	HP	Stage	Outlet Size in mm	m ³ /hr lps	0	19.3	45.7	65.3	77.1	86.1	100	121.7	123.3
						0	5.63	12.7	18.15	21.43	23.92	27.79	33.8	34.26
WC8CM-68/20/4	15	20	4	100	Head in Metres	87.1	81.02	76.07	71.21	66.35	61.42	51.58	31.9	11.95

Model	kW	HP	Stage	Outlet Size in mm	m ³ /hr lps	0	20	30	40	50	60	75	80	90	100	110	120
						0	5.55	8.33	11.11	13.88	16.66	20.83	22.22	25	27.78	30.55	33.33
WC8CM-68/25/4	18.5	25	4	100	Head in Metres	88	80	77	75	73	70	64	61	55	48	39	28

Model	kW	HP	Stage	Outlet Size in mm	m ³ /hr lps	0	18	22	27	33	39	45	50	57	63	68	75	81	87	93
						0	5	6	7.5	9.2	10.8	12.5	14	15.8	17.5	19	20.8	22.5	24.2	25.8
WC8CM-80/17.5/03	13	17.5	3	100	Head in Metres	68	64	63	61	60	58	57	56	54	53	51	49	47	44	41
WC8CM-90/12.5/02	9.3	12.5	2	100		46	43	42	41	41	40	39	38.5	38	37	36	35	33	32	30
WC8CM-90/15/02	11	15	2	100		54	50	49	48	47	46	45	44	42	41	40	39	37	36	34
WC8CM-90/17.5/02	13	17.5	2	100		54	51	50	49	48	47	44	43	42	41.5	41	40.5	40	39.5	39
WC8CM-90/20/03	15	20	3	100		77	70	69	67	65	64	62	61	60	58	57	55	53	51	49
WC8CM-90/25/03	18.5	25	3	100		81	80	79	77	75	72	70	68	66	63	62	60	59	57	55

Model	kW	HP	Stage	Outlet Size in mm	m ³ /hr lps	0	18	22	27	33	39	45	50	57	63	75	87	99	104	111
						0	5	6	7.5	9.2	10.8	12.5	14	15.8	17.5	20.8	24.2	27.5	29	30.8
WC8CM-100/20/02	15	20	2	100	Head in Metres	56	54	53	52	51	49	46	44	42	41	40.5	40	39	38	34

Model	kW	HP	Stage	Outlet Size in mm	m ³ /hr lps	0	20	30	40	50	60	65	68	70	80	90	100
						0	5.55	8.33	11.11	13.88	16.66	18.05	18.88	19.44	22.22	25	27.78
WC8CM-58/7.5/03(SPL)	5.5	7.5	3	100	Head in Metres	52	47	44	42	37	32	30	28	27	21	15	9
WC8CM-65/10/03(SPL)	7.5	10	3	100		66	58	55	52	49	45	42	41	40	34	28	21
WC8CM-65/12.5/04(SPL)	9.3	12.5	4	100		80	72	69	65	60	54	51	49	47	41	33	24
WC8CM-68/12.5/03(SPL)	9.3	12.5	3	100		71	65	62	59	55	52	50	48	47	41	35	28

PERFORMANCE CHART

200mm / 250mm BOREWELL SUBMERSIBLE PUMPSETS - **CONGO Series**

2900 RPM, At Rated Voltage – **Three Phase** 415 Volts, 50Hz, A.C. Supply, Maximum Outer Diameter : **247 mm**

MIXED FLOW

Model	kW	HP	Stage	Outlet Size in mm	m³/hr lps	0	18	36	54	72	90	108	126	144	162	180	198	216
						0	5	10	15	20	25	30	35	40	45	50	55	60
CMA0/40/02	30	40	2	150	Head in Metres	68	66	64	62	60	58	55	52	48	44	39	33	25
CMA0/60/03	45	60	3	150		102	100	97	94	91	88	83	77	72	65	57	48	33
CMA0/75/04	55	75	4	150		128	125	122	118	114	110	105	99	93	90	80	70	52
CMA0/100/05	75	100	5	150		162	158	154	150	145	140	132	126	120	110	95	80	60

MATERIAL OF CONSTRUCTION - PUMP			
175mm (7") Pump		200mm (8") Pump	250mm (10") Pump
Part Name	Material	Material	Material
Check valve housing	Cast iron	Cast iron	Cast iron
Check valve seat	Nitrile butyl rubber	SG iron	Nitrile Butyl Rubber / SG Iron
Diffuser chamber	Cast iron	Cast iron	Cast iron
Impeller	SS 410	SS 410	LTB 2 & SS 410
Suction inter connector	Cast iron	Cast iron	Cast iron
Inlet screen	SS 202	SS 202	SS 202
Pump shaft	SS 410 / SS 431	SS 410 / SS 431	SS 410 / SS 431
Cable guard	SS 202	SS 202	SS 202
Coupling	SS 410	SS 410 / SS 431	SS 410 / SS 431

MATERIAL OF CONSTRUCTION - MOTOR		
150mm (6") Motor		200mm (8") Motor
Part Name	Material	Material
Upper and lower housing	Cast iron	Cast iron
Stator shell	Stainless Steel	Stainless Steel
Shaft	SS 410 & EN 9 with 304	EN 8 with SS 410 / 431 sleeve at bush guide
Journal bushes	LTB - 4	LTB - 4
Thrust assembly	SS 420 and Graphite carbon	SS 420 and Graphite carbon
Diaphragm	High nitrile butyl rubber	High nitrile butyl rubber



C.R.I. PUMPS

Pumping trust. Worldwide.

-
- 5 decades of engineering excellence ● Sold in more than 120 countries
 - More than 6000 models of pumps and motors ● Over 1500 service centres
 - Fully equipped R&D wing recognized by Ministry of Science and Technology
 - ISO 9001 & 14001 accreditations
-

TOLL FREE 1800 200 1243

 www.crigroups.com  www.facebook.com/cripumps

 www.twitter.com/cri_pumps

