

HIGH-PRESSURE R.O. PUMPS



C.R.I. PUMPS • PIPES • WIRES & CABLES • SOLAR



C.R.I. HIGH-PRESSURE R.O. PUMPS

DESCRIPTION

C.R.I's ClaRO Series Pumps are specially designed to deliver high pressure water in R.O. application. These pumps are powered by a Totally Enclosed Fan Cooled, A.C. induction motor which is suitable for continuous duty. Motor stator is made of low watt loss steel laminations assembled under pressure and rigidly locked in the frame. Dynamically balanced rotor ensures vibration and noise free operations. The windings are made of enamelled copper wire offers excellent resistance. The specially designed unique type mechanical seal is used to withstand in high TDS water applications.

SPECIFICATIONS

Power Range	: 0.37 kW - 1.1 kW (0.5 HP - 1.5 HP)
Head Range	: 10 Mtrs to 130 Mtrs
Flow Range	: 5 LPM to 54 LPM
Version	: Single Phase, 230V, 50Hz, A.C. Supply
Max. Working Pressure	:13 bar
Insulation Class	:В
Degree of Protection	:IP 44
Pipe Size	: 15 x 15 mm and 25 x 25mm

APPLICATIONS

- Water Treatment Plant
- Pressure Boosting Systems

Cla**R**6


- Residential & Gardening
- Hot & Cold Water Circulation

MATERIAL OF CONSTRUCTION

	Motor Frame	:	Aluminium
	Front & Back Cover	:	CI
	Mechanical Seal	:	Carbon vs Ceramic
	Impeller	:	Brass
	Shaft	:	SS410
-		_	

PERFORMANCE CURVE

PERFORMANCE CHART



2880 RPM, SINGLE PHASE - 230 VOLTAGE , 50 HZ, A.C. SUPPLY

			SUCTION	ICTION TOTAL HEAD IN									N METER					
MODEL	kW	НР	X DELIVERY	10	20	30	40	50	60	70	80	90	100	110	120	130		
			IN MM	DISCHARGE IN LPM														
ClaRO 50	0.37	0.5	15x15	35	30.5	24.5	19.5	15.5	11	6								
ClaRO 100	0.75	1.0	15x15	37	33	28.2	23	20.5	16	12	9	5						
ClaRO 150	1.1	1.5	25x25	54	53	50	48	42	38	32	28	23	21	13	9.5	5.5		
		γ					·)	//					1/		()			